



Custom Industrial Nylon 6 GF30 Tube Engineering Plastic Co. Ltd

Basic Information

Place of Origin: China

Brand Name: MAKEWELL

• Certification: ISO9001 Rohs, Reach

Model Number: Nylon PA6 GF30

Minimum Order

Quantity:

10kg

Price: Negociation Packaging Details: Pallet

• Delivery Time: 7-15 days

• Payment Terms: L/C, D/A, D/P, T/T, Western Union,

MoneyGram

• Supply Ability: 100000000 kg /month



Product Specification

Product: Custom Cnc Machining Engineering Plastic

Products

Flammability: UL 94 V-2
 Density: 1.14 G/cm³
 Service: OEM/ODM

• Size: 15-100mm Diameter

Material: Nylon 6 GF30Type: Sheet, Rod, Tube

Color: NC/BLACK

• Highlight: Makewell Custom Nylon 6 GF30,

Makewell industrial Nylon 6 GF30,

Makewell Nylon6 engineering plastic co ltd

Product Description:

Nylon 6 GF30 is a custom engineering plastic product provided by Plastic Engineering Inc. It is made from nylon 66 and has a high glass fiber content of 30%. This material is highly versatile and can be used to create a variety of shapes such as sheets, rods, and tubes. It has a density of 1.14 g/cm³ and is UL 94 V-2 rated for flammability. Nylon 6 GF30 offers excellent strength, toughness, and wear resistance. It is resistant to most oils, solvents, and chemicals. The material is highly customizable and can be machined with precision to meet the exact requirements of your application. Nylon 6 GF30 is ideal for a wide range of industrial applications such as automotive, aerospace, and medical. Plastic Engineering Inc. offers OEM and ODM services to ensure your nylon engineering plastic product meets your exact specifications.

Features:

Product Name: Nylon 6 GF30

Service: OEM/ODM
Type: Sheet, Rod, Tube
Flammability: UL 94 V-2
Material: Nylon 6 GF30
Density: 1.14 G/cm³

Speciality: Plastic Engineering Inc, Plastics Engineering Co, Custom Plastic Fabrication

Technical Parameters:

Property	Value
Size	15-100mm Diameter
Туре	Sheet, Rod, Tube
Material	Nylon 6 GF30
Service	OEM/ODM
Color	NC/BLACK
Flammability	UL 94 V-2
Product	Custom Cnc Machining Engineering Plastic Products
Density	1.14 G/cm ³

Applications:

MAKEWELL's Nylon PA6 GF30 is the perfect choice for any engineering plastic nylon needs. The material has excellent properties such as flammability (UL 94 V-2) and density (1.14 G/cm³). It is also available in sheet, rod and tube types with sizes ranging from 15-100mm diameter. It has obtained ISO 9001, Rohs, Reach certifications from plastic engineering inc. and is the perfect material for any application requiring the strength, toughness and wear resistance of engineering nylon 6. It has a minimum order quantity of 10kg and the price is negotiable. The packaging is pallet and delivery time is 7-15 days with payment terms including L/C, D/A, D/P, T/T, Western Union, MoneyGram. The supply ability is up to 100000000 kg per month. MAKEWELL's Nylon PA6 GF30 is the perfect choice for any engineering nylon 6 needs, and it comes with the assurance of OEM/ODM service.

Customization:

MAKEWELL offers custom Nylon PA6 GF30 engineering plastic products for your specific needs. Our products are ISO9001 Rohs, Reach certified and have a minimum order quantity of 10kg. We accept payment via L/C, D/A, D/P, T/T, Western Union, MoneyGram. Our supply ability is 100000000 kg per month. Our products are made from nylon engineering plastic and are custom-made through CNC machining. We offer sheet, rod, and tube products with a density of 1.14 G/cm³. The flammability rating is UL 94 V-2. We are able to provide OEM/ODM services to meet your specific requirements.

Support and Services:

Technical Support and Service for Nylon 6 GF30: Guidance and advice on product selection Trouble-shooting and problem solving Product application advice Product training and demonstrations On-site support and maintenance

Technical assistance and customer service

Free product samples

MakeWell Changzhou Makewell Industry Co., Ltd

+86-18626201100

info@makewellcz.com



makewellplastic.com

Gounan Industrial Pack Wujin District Changzhou City, Jiangsu, China