

Engineering Plastic Nylon 6 GF30 Sheet Bar 30mm

Basic Information

- Place of Origin:
- Brand Name: MAKEWELL
- Certification: ISO9001 Rohs, Reach

China

- Model Number: Nylon PA6 GF30
- Minimum Order 10kg
 Quantity:
- Price: Negociation
- Packaging Details: Pallet
- Delivery Time: 7-15 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
 Supply Ability: 10000000 kg /month

Product Specification

• Type:	Sheet, Rod, Tube
• Flammability:	UL 94 V-2
Color:	NC/BLACK
Material:	Nylon 6 GF30
Density:	1.14 G/cm ³
• Size:	15-100mm Diameter
Product:	Custom Cnc Machining Engineering Plastic Products
Service:	OEM/ODM
Highlight:	Makewell Engineering Nylon 6 GF30, Makewell Nylon 6 GF30 Sheet, Makewell Engineering 30mm nylon bar

Product Description:

Nylon 6 GF30 is an engineering nylon manufactured by Plastic Engineering Inc. with excellent flammability rating of UL 94 V-2 and density of 1.14 G/cm³. It comes in various forms such as sheets, rods, tubes and has a wide range of colors including NC/BLACK. It is widely used in custom Cnc machining and engineering plastic products. Nylon 6 GF30 has many advantages such as high strength, excellent heat and chemical resistance, low moisture absorption, good dimensional stability, and flame retardancy.

Features:

Product Name: Nylon 6 GF30 Color: NC/BLACK Size: 15-100mm Diameter Service: OEM/ODM Type: Sheet, Rod, Tube Material: Nylon 6 GF30 Plastic Engineering Inc.: Nylon Engineering Plastic, Engineering Nylon, High Strength and Wear Resistance.

Technical Parameters:

Property	Value
Density	1.14 G/cm ³
Material	Nylon 6 GF30
Туре	Sheet, Rod, Tube
Size	15-100mm Diameter
Service	OEM/ODM
Flammability	UL 94 V-2
Product	Custom Cnc Machining Engineering Plastic Products
Color	NC/BLACK

Applications:

MAKEWELL's Nylon PA6 GF30 is a high-performance engineering plastic product with excellent mechanical and electrical properties. It is perfect for applications where durability and strength are needed, such as in automotive, aerospace, and other manufacturing industries. Its high strength-to-weight ratio makes it an ideal choice for components requiring structural strength and dimensional stability. It is also resistant to corrosion, chemicals, ultraviolet radiation, and weathering, making it a great choice for outdoor applications. Its density of 1.14 g/cm³ makes it lighter than other engineering plastics, while its excellent surface finish makes it an ideal candidate for custom CNC machining. It is available in sheet, rod, and tube forms in a variety of sizes from 15 to 100 mm diameter, and can be customized with colors such as NC/Black.

MAKEWELL's Nylon PA6 GF30 is an ISO9001, Rohs, and Reach certified engineering plastic product. It is available in minimum orders of 10 kg, with delivery times of 7-15 days. It can be purchased with payment terms of L/C, D/A, D/P, T/T, Western Union, and MoneyGram. Its supply ability is 100000000 kg/month. Packaging is done in pallets to ensure safe delivery.

Customization:

MAKEWELL Nylon PA6 GF30 Custom Cnc Machining Engineering Plastic Products

Brand Name: MAKEWELL Model Number: Nylon PA6 GF30 Place of Origin: China Certification: ISO9001 Rohs, Reach Minimum Order Quantity: 10kg Price: Negotiation Packaging Details: Pallet Delivery Time: 7-15 days Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram Supply Ability: 10000000 kg /month Size: 15-100mm Diameter Flammability: UL 94 V-2 Material: Nylon 6 GF30 Product: Custom Cnc Machining Engineering Plastic Products Type: Sheet, Rod, Tube MAKEWELL offers custom cnc machining services for engineering nylon and engineering plastic products. Our engineering plastics manufacturing services provide high-precision custom CNC machining for engineering plastics with the highest quality standards. We use nylon 6 GF30 material to produce rod, sheet and tube products with size ranging from 15-100mm in diameter. The products are UL 94 V-2 flammability rated and certified with ISO9001, Rohs and Reach. The minimum order quantity is 10kg and the price is negotiable. We are able to deliver 7-15 days and accept payment with L/C, D/A, D/P, T/T, Western Union and MoneyGram. Our supply ability is up to 100000000 kg per month.

Support and Services:

Technical Support and Services for Nylon 6 GF30

We offer technical support and services for our Nylon 6 GF30 product. Our team of experienced professionals can provide you with valuable and reliable advice on how to best use the product in your applications. We offer a wide range of services, including: Product selection advice

Design and engineering assistance

Product application support

Troubleshooting and problem solving

Customized product development

We are committed to providing the highest level of customer service and support. Please contact us if you have any questions or need assistance with our Nylon 6 GF30 product.

