



Engineering White PTFE GF25 Plastic Sheet OEM For Medical

Our Product Introduction

for more products please visit us on makewellplastic.com

Basic Information

- Place of Origin: China
- Brand Name: MAKEWELL
- Certification: ISO9001 Rohs, Reach
- Model Number: PTFE GF25
- Minimum Order Quantity: 10kg
- Price: Negotiation
- Packaging Details: Pallet
- Delivery Time: 7-15 days
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram
- Supply Ability: 100000000 kg /month



Product Specification

- Thermal Conductivity: 0.25 W/m-K
- Filler Content: 25%
- Hardness: 75 Shore D
- Product Name: PTFE GF25
- Filler: Glass Fiber Reinforced
- Material: PTFE
- Tensile Strength: 1,000 Psi
- Physiologically Safe: Good
- Highlight: **Engineering PTFE GF25, White PTFE GF25, OEM ptfе plastic sheet**

Product Description

Product Description:

PTFE GF25 is one of the special engineering plastics featuring excellent properties such as physiologically safe, high hardness and good OD. It is a premium plastic engineering product that has a hardness of 75 Shore D and an OD of 1-1/8 inch. This product is available in both black and white color, which can meet different needs. It is also highly durable and has a long service life. With its excellent performance, PTFE GF25 is widely used in various demanding applications, especially in industries such as aerospace, automotive, and medical.

Features:

Product Name: PTFE GF25

Tensile Strength: 1,000 Psi

Color: Black, White

Operating Temperature: -200°C To +260°C

Material: PTFE

OD: 1-1/8 Inch

Keywords: PE PTFE PP, Plastic Engineering Products, PE PTFE PP Supplier

Technical Parameters:

Property	Value
Product Name	PTFE GF25
Material	PTFE
Tensile Strength	25 MPa / 1,000 Psi
Flexural Strength	20 MPa
Hardness	75 Shore D
Filler Content	25%
Filler	Glass Fiber Reinforced
Low Reactivity	Good
Physiologically Safe	Good

Applications:

MAKEWELL PTFE GF25 is a high-performance material made of polytetrafluoroethylene (PTFE). It is renowned for its excellent chemical resistance and low coefficient of friction. It has superior properties such as high tensile strength, hardness, and flexural strength. Its operating temperature ranges from -200°C to +260°C, making it suitable for a wide range of applications. It is also certified by ISO9001 Rohs and Reach. The minimum order quantity is 10kg and the package is pallet. The payment terms include L/C, D/A, D/P, T/T, Western Union, and MoneyGram. MAKEWELL PTFE GF25 is available in large quantities and can be delivered within 7-15 days. It is an ideal choice for high-end applications such as PE PTFE PP and Nylon PTFE.

Customization:

MAKEWELL PTFE GF25 is a customized product with a number of key features, including:

Brand Name: MAKEWELL

Model Number: PTFE GF25

Place of Origin: China

Certification: ISO9001 Rohs, Reach

Minimum Order Quantity: 10kg

Price: Negotiation

Packaging Details: Pallet

Delivery Time: 7-15 days

Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram

Supply Ability: 100000000 kg /month

OD: 1-1/8 Inch

Tensile Strength: 25 MPa

Material: PTFE

Thermal Conductivity: 0.25 W/m-K

Physiologically safe: Good




Nylon PTFE, PE PTFE PP, PE PTFE PP PTFE: Excellent

MAKEWELL PTFE GF25 is a great option for high-quality, customized PTFE products.

Support and Services:

PTFE GF25 Technical Support and Service:
24/7 technical support for product installation and usage.
Troubleshooting and problem diagnosis.
Expert advice on product selection and application.
Software updates and compatibility issues.
Guidance on product warranty and maintenance.

 **Changzhou Makewell Industry Co., Ltd**

 +86-18626201100  info@makewellcz.com  makewellplastic.com

Gounan Industrial Park Wujin District Changzhou City, Jiangsu, China