

# Custom Industrial Nylon 6 GF30 Tube Engineering Plastic Co. Ltd

Basic Information			
Place of Origin:	China		
Brand Name:	MAKEWELL		
Certification:	ISO9001 Rohs, Reach		
Model Number:	Nylon PA6 GF30		
<ul> <li>Minimum Order Quantity:</li> </ul>	10kg		
Price:	Negociation		
Packaging Details:	Pallet		
Delivery Time:	7-15 days		
Payment Terms:	L/C, D/A, D/P, T/T, Western Union, MoneyGram		
Supply Ability:	100000000 kg /month		



## Product Specification

Product:	Custom Cnc Machining Engineering Plastic Products
Flammability:	UL 94 V-2
Density:	1.14 G/cm <sup>3</sup>
Service:	OEM/ODM
• Size:	15-100mm Diameter
Material:	Nylon 6 GF30
• Type:	Sheet, Rod, Tube
Color:	NC/BLACK
Highlight:	Makewell Custom Nylon 6 GF30, Makewell industrial Nylon 6 GF30, Makewell Nylon6 engineering plastic co Itd

#### **Product Description:**

Nylon 6 GF30 is a custom engineering plastic product provided by Plastic Engineering Inc. It is made from nylon 66 and has a high glass fiber content of 30%. This material is highly versatile and can be used to create a variety of shapes such as sheets, rods, and tubes. It has a density of 1.14 g/cm<sup>3</sup> and is UL 94 V-2 rated for flammability. Nylon 6 GF30 offers excellent strength, toughness, and wear resistance. It is resistant to most oils, solvents, and chemicals. The material is highly customizable and can be machined with precision to meet the exact requirements of your application. Nylon 6 GF30 is ideal for a wide range of industrial applications such as automotive, aerospace, and medical. Plastic Engineering Inc. offers OEM and ODM services to ensure your nylon engineering plastic product meets your exact specifications.

### **Features:**

Product Name: Nylon 6 GF30 Service: OEM/ODM Type: Sheet, Rod, Tube Flammability: UL 94 V-2 Material: Nylon 6 GF30 Density: 1.14 G/cm<sup>3</sup> Speciality: Plastic Engineering Inc, Plastics Engineering Co, Custom Plastic Fabrication

## **Technical Parameters:**

Property	Value
Size	15-100mm Diameter
Туре	Sheet, Rod, Tube
Material	Nylon 6 GF30
Service	OEM/ODM
Color	NC/BLACK
Flammability	UL 94 V-2
Product	Custom Cnc Machining Engineering Plastic Products
Density	1.14 G/cm <sup>3</sup>

### **Applications:**

MAKEWELL's Nylon PA6 GF30 is the perfect choice for any engineering plastic nylon needs. The material has excellent properties such as flammability (UL 94 V-2) and density (1.14 G/cm<sup>3</sup>). It is also available in sheet, rod and tube types with sizes ranging from 15-100mm diameter. It has obtained ISO 9001, Rohs, Reach certifications from plastic engineering inc. and is the perfect material for any application requiring the strength, toughness and wear resistance of engineering nylon 6. It has a minimum order quantity of 10kg and the price is negotiable. The packaging is pallet and delivery time is 7-15 days with payment terms including L/C, D/A, D/P, T/T, Western Union, MoneyGram. The supply ability is up to 10000000 kg per month. MAKEWELL's Nylon PA6 GF30 is the perfect choice for any engineering nylon 6 needs, and it comes with the assurance of OEM/ODM service.

#### **Customization:**

MAKEWELL offers custom Nylon PA6 GF30 engineering plastic products for your specific needs. Our products are ISO9001 Rohs, Reach certified and have a minimum order quantity of 10kg. We accept payment via L/C, D/A, D/P, T/T, Western Union, MoneyGram. Our supply ability is 100000000 kg per month. Our products are made from nylon engineering plastic and are custom-made through CNC machining. We offer sheet, rod, and tube products with a density of 1.14 G/cm<sup>3</sup>. The flammability rating is UL 94 V-2. We are able to provide OEM/ODM services to meet your specific requirements.

#### Support and Services:

Technical Support and Service for Nylon 6 GF30: Guidance and advice on product selection Trouble-shooting and problem solving Product application advice Product training and demonstrations On-site support and maintenance Technical assistance and customer service

Free	product	samp	les
------	---------	------	-----

